

WareDose 10 is a dosing system in a new SEKO outlook, with LED display, using potentiometers and DIP switches settings.



### FEATURES:

- **Selectable power supply 24 - 115 - 230 Vac**
- **IP65** Protection degree and class II electrical insulation
- **ON/OFF** switch
- **Level Control Inputs.**
- **Analogic Speed Control (15-100%) of Det and Rinse pump via potentiometer on the board**
- **Manual Priming** of the pumps via buttons on frontal panel
- Features **new PC front cover with easy opening and stop in open position**
- New ABS polished enclosure with easy opening by frontal keys
- **3 Rollers and ball bearing** on motor shaft ensure 20% higher lifetime on tube and motor
- Robust plastic hinge not affected by corrosion.

### TECHNICAL FEATURES

TYPE	WareDose 10
CODE	WDO10040100Y0000
CERTIFICATIONS	CE, EAC
INTERFACE	Analogue with LED display
PROTECTION DEGREE	IP65
ELECTRICAL CLASS	Class II (ground connection not needed)
POWER SUPPLY	24 – 115 – 230 Vac (selectable by jumper)
CONSUMPTION	15 W
CASE MATERIAL	ABS

HYDRAULIC DATA	
DETERGENT PUMP FLOW RATE	1 - 4 l/h
RINSE AID PUMP FLOW RATE	0,15 – 1 l/h
RINSE PUMP MAX WORKING BACKPRESSURE	3 bar
DETERGENT PUMP SQUEEZE TUBE	Santoprene (6x10)
RINSE PUMP SQUEEZE TUBE	Sekobril (3x8)
EXTERNAL TUBE FITTINGS	For tube 4x6 with nuts (others upon request)

### DIMENSIONAL DRAWINGS

