

WareDose 20 is a dosing system in a new SEKO outlook, designed to dispense chemicals to door and conveyor-type ware-washing machines by using an advanced technology to meter precise amounts of product



FEATURES:

- **Selectable power supply** 24 - 115 - 230 Vac
- **IP65** Protection degree and class II electrical insulation
- **ON/OFF** switch
- **Separated Level Control Inputs**
- **Analogic Speed Control (15-100%)** of Det and Rinse Aid pump on rinse signal via potentiometer on the board. **Analogic Time control (0-200 sec) of Det dosing on 1st charge signal** via potentiometer.
- **Manual Priming** of the pumps via buttons on frontal panel
- Features **new PC front cover with easy opening and stop in open position**
- New ABS polished enclosure with easy opening by frontal keys
- **3 Rollers and ball bearing** on motor shaft ensure 20% higher lifetime on tube and motor
- Robust plastic hinge not affected by corrosion.

TECHNICAL FEATURES

| TECHNICAL FEATURES | |
|--------------------|---|
| TYPE | WareDose 20 |
| CODE | WDO20040100Y0000 |
| CERTIFICATIONS | CE, EAC |
| INTERFACE | Analogue with LED display |
| PROTECTION DEGREE | IP65 |
| ELECTRICAL CLASS | Class II (ground connection not needed) |
| POWER SUPPLY | 24 – 115 – 230 Vac (selectable by jumper) |
| CONSUMPTION | 15 W |
| CASE MATERIAL | ABS |

| HYDRAULIC DATA | |
|-------------------------------------|--|
| DETERGENT PUMP FLOW RATE | 1 - 4 l/h |
| RINSE AID PUMP FLOW RATE | 0,15 – 1 l/h |
| RINSE PUMP MAX WORKING BACKPRESSURE | 3 bar |
| DETERGENT PUMP SQUEEZE TUBE | Santoprene (6x10) |
| RINSE PUMP SQUEEZE TUBE | Sekobril (3x8) |
| EXTERNAL TUBE FITTINGS | For tube 4x6 with nuts (others upon request) |

DIMENSIONAL DRAWINGS

