


dynamik

analoge peristaltic dosing pumps

TRANSAXLE
TECHNOLOGY
inside
by
SEKO



SEKO Asia Pacific **SINGAPORE** • SEKO China **CHINA** • SEKO do Brasil **BRAZIL** • SEKO Dosing Systems **USA** • SEKO Southern Africa **SOUTH AFRICA** • SEKO Deutschland **GERMANY** • SEKO France **FRANCE** • SEKO Iberica **SPAIN** • SEKO Italia **ITALY** • SEKO SIETA **ROMANIA** • OOO SEKO **RUSSIA** • SEKO UK **UNITED KINGDOM**

www.seko.com

innovation > technology > future

dynamik Analogue version



Precise programming of speed, time and conductivity value by last generation trimmers and microprocessor technology

Improved lifetime of squeeze tube and motor thanks to the Transaxle Technology and to new technology tubing

IP 65 enclosure: Made of PP reinforced with glass fiber so that it is extremely water and dust proof. Seko's standard construction technology continues to provide products with high resistance to impacts and the chemical agents

Electrical class 2: Making a ground cable connection unnecessary. No external metal parts come into contact with the operator

Materials: The entire range is made using fire-retardant materials and RoHS technology. **This allows to avoid lead or other heavy materials in contact with operator**

Wide range of options: All pumps can be supplied with the possibility of connecting a level probe, acoustic alarm and priming by means of a switch



Detergent

NPA

Fixed speed peristaltic pump with analogic dosing adjustment by conductivity probe

Power supply from 90 to 265 Vac 50-60 Hz (24 Vac 50-60 Hz upon request) • **Power consumption** 3.5 W

NPA 6 (sekoflex squeeze tube)	0.1 bar	6 lt/h
NPA 9 (sekoflex squeeze tube)	0.1 bar	9 lt/h

NPR

Peristaltic pump with analogic speed adjustment

Power supply automatic switching from 90 to 265 Vac 50-60 Hz (24 Vac 50-60 Hz upon request) • **Power consumption** 3.5 W

NPR 4 (sekoflex squeeze tube)	0.1 bar	0.6...4 lt/h
NPR 7 (sekoflex squeeze tube)	0.1 bar	1.2...7 lt/h

NPE 0.4

Fixed speed peristaltic pump

Power supply 230 Vac 50-60 Hz (24 Vac 50-60 Hz upon request) • **Power consumption** 3.5 W

NPE 0.4 (sekobril squeeze tube)	3 bar	0.4 lt/h
--	--------------	-----------------

NPR 1

Peristaltic pump with analogic speed adjustment

Power supply from 90 to 265 Vac 50-60 Hz (24 Vac 50-60 Hz upon request) • **Power consumption** 3.5 W

NPR 1 (sekobril squeeze tube)	3 bar	0.2...1 lt/h
--------------------------------------	--------------	---------------------

NPE

Fixed speed peristaltic pump

Power supply 230 Vac 50-60 Hz (24 Vac 50-60 Hz upon request) • **Power consumption** 3.5 W

NPE 1.5 (sekoflex squeeze tube)	0.1 bar	1.5 lt/h
NPE 3 (sekoflex squeeze tube)	0.1 bar	3 lt/h

NRT

Fixed speed peristaltic pump with analogic adjustment of dosing time. Models powered via single or double solenoid valves available. Two setting trimmers enable detergent Initial Charge and Make Up Charge.

Power supply from 90 to 265 Vac 50-60 Hz (24 Vac 50-60 Hz upon request) • **Power consumption** 3.5 W • **Initial Charge time:** 18 to 180 s • **Make Up Charge time:** 2 to 15 s

NRT 6 (sekoflex squeeze tube)	0.1 bar	6 lt/h
NRT 9 (sekoflex squeeze tube)	0.1 bar	9 lt/h

Rinse Aid

NPM

Fixed speed peristaltic pump with analogic adjustment of dosing time. A trimmer enable rinse aid dosing time.

Power supply from 90 to 265 Vac 50-60 Hz (24 Vac 50-60 Hz upon request) • **Power consumption** 3.5 W • **Dosing Time** 1 to 25 s

NPM 0.4 (sekobril squeeze tube)	3 bar	0.4 lt/h
NPM 1.5 (sekobril squeeze tube)	3 bar	1.5 lt/h