



### Peristaltic pump *Kronos 50 cond*

Part number.: **KRCR0210M6000**

With stepper motor <35dB

LCD Display 16x2

Manual mode – Ton/Toff – Delay – Signal

Conductivity Mode – mS

Calibration of the electrode

Temperature compensation

### Technical properties

|                   |   |
|-------------------|---|
| Cabinet           | PP, protection IP 65                              |
| Performance       | 10 - 10000 ml/h, stepless adjustment              |
| Head              | 2 bar   |
| Priming           | 15 m  |
| Measuring range   | 0,10 to 15 mS                                     |
| Probe             | K1 conductivity probe , option PT100              |
| Pump Tubing       | SekoMed 6,25x10,65 mm / Pharmed / Shore 70 *      |
| Connections       | Screw with nut 4 x 6 mm                           |
| Power supply      | 100 - 240 VAC / 50 - 60 Hz                        |
| Power consumption | 20 W  |
| Fuse              | 1,6 A   |
| Delivery          | Includes conductivity probe (no installation kit) |
| Dimensions        | 210mm x 118mm x 143 (H x W x L)                   |
| Weight            | 2,2 kg  |
| Standards         | 73/23EEC of 19/02/73                              |
|                   | 89/336EEC of 03/05/89                             |
|                   | EN60336-1   |

\*Option: **sekoExtra** (dual layer type) / 6,25x10,65 mm / Shore 55

**F4040** (Tygon) / 6,25x10,65 mm / Shore 57



Kidnakken 11  
DK-4930 Maribo - Danmark

Tlf.: +45 54 75 75 45, Fax: +45 54 74 75 45  
info@reciprotor.com, www.reciprotor.com

