



Peristaltik-Pumpe kronos 50 full

Part number: **KRFM0210M6000**

with stepper motor <35dB

LCD display 16x2

Manual mode –Ton/Toff – delay - signal

mA mode 4-20 mA or 20-4 mA

PPM mode

Batch mode

1:N or N:1 mode

Technical properties

Cabinet	PP, protection IP 65
Performance	10- 10000 ml/h, stepless adjustment
Head	2 bar
Priming	15 m
Pump tube	SekoMed 6,25 x10,65 mm / pharmed / Shore 55 *
Connections	Screw with nut 4 x 6 mm
Power supply	100 - 240 VAC / 50 – 60 Hz
Power consumption	20 W
Fuse	1,6 A
Delivery	Without installation kit
Dimensions	210mm x 118mm x 143 (H, W, L)
Weight	2,2 Kg
Standards	73/23EEC of 19/02/73
	89/336EEC of 3/05/89
	EN60336-1

*Option: **SekoExtra** 6,25 x 10,65 mm / Shore 55

F4040 (Tygon) / 6,25 x 10,65 mm / Shore 57



Kidnakken 11
DK-4930 Maribo - Danmark

Tlf.: +45 54 75 75 45, Fax: +45 54 74 75 45
info@reciprotor.com, www.reciprotor.com

