



**Peristaltik-Pumpe kronos 50 full**

Part number: **KRFM0302M5000**

with stepper motor <35dB

LCD display 16x2

Manual mode –Ton/Toff – delay - signal

mA mode 4-20 mA or 20-4 mA

PPM mode

Batch mode

1:N or N:1 mode

**Technical properties**

|                   |  |
|-------------------|--|
| Cabinet           | PP, protection IP 65                       |
| Performance       | 2 - 2000 ml/h, stepless adjustment         |
| Head              | 3 bar                                      |
| Priming           | 15 m                                       |
| Pump tube         | sekoExtra 3x7,4 mm / Norprene / Shore 55 * |
| Connections       | Screw with nut 4 x 6 mm                    |
| Power supply      | 100 - 240 VAC / 50 - 60 Hz                 |
| Power consumption | 20 W                                       |
| Fuse              | 1,6 A                                      |
| Delivery          | Without installation kit                   |
| Dimensions        | 210mm x 118mm x 143 (H, W, L)              |
| Weight            | 2,2 Kg                                     |
| Standards         | 73/23EEC of 19/02/73                       |
|                   | 89/336EEC of 3/05/89                       |
|                   | EN60336-1                                  |

\*Option: **F4040** (Tygon) / 3x7,4 mm / Shore 57



Kidnakken 11  
DK-4930 Maribo - Danmark

Tlf.: +45 54 75 75 45, Fax: +45 54 74 75 45  
info@reciprotor.com, www.reciprotor.com

